



2 by 4 Lumber Sales

211 Gallagher Ridge Road, Gallagher Ridge NB E1G 3A6
Phone 506-857-2294 email 2by4lumber@gmail.com

High Output 6.5 Peak HP 60 Gallon Air Compressor

Product Features:

- Thermally protected US Motors® 6.5 peak HP motor with reset
- 3 cylinder cast iron single stage oil lubricated pump
- High output 18.5 CFM @ 100 PSI
- 150 PSI Max pressure for optimum tool performance
- 60 Gallon ASME registered tank provides longer run times
- ASME safety valve
- Belt drive with sturdy enclosed metal belt guard
- Large intake filters
- Heavy-duty 1/2" ball valve and easy to read tank pressure gauge
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life
- High efficiency reed valves for maximum performance



MODEL	KC-5160V3
MOTOR (PEAK)	6.5 HP
FACTORY PRESSURE SETTING (ADJUSTABLE UP TO)	95-125 PSI (Max 135 PSI)
MAXIMUM PRESSURE	150 PSI
AIR DELIVERY @ 40 PSI	22.6 CFM
AIR DELIVERY @ 100 PSI	18.5 CFM
TANK SIZE	60 Gallon
MOTOR AMPERAGE	23 Amp.
RPM	3,450
VOLTAGE	240V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	25" x 22" x 68" / 280 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	31" x 24" x 73" / 290 lbs
UPC	7 72995 01100 1

Specifications subject to change.

See our lineup at www.2by4lumber.com